

Product certificate
K6336/10

Issued 2011-09-01
Replaces K6336/09
Page 1 of 3


Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Sanitärtechnik Eisenberg GmbH

complying with the technical specifications as laid down in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate, on delivery, may be relied upon to comply with Kiwa evaluation guideline BRL-K620/04 "Flushing cisterns".



Bouke Meekma
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V
Sir W. Churchill-laan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 70 414 44 00
Fax +31 70 414 44 20
E-mail info@kiwa.nl
www.kiwa.nl

Supplier

Sanitärtechnik Eisenberg GmbH
Gewerbegebiet – Inder Wiesen 8
P.O. box 1149
D-07601 Eisenberg / Thüringen
Germany
Telephone +49 366 91 598-0
Telefax +49 366 91 59815
E-mail info@sanit.de
www.sanit.de

Certification process
consists of initial and
regular inspection of:

- quality system
- product

Flushing cisterns

Product specification

The products mentioned below belong to this certificate

High level cistern, 6 ± 0.2 or 7 to 8 litres

no. 925, high level

Flushing volume 8 litres, side connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

Low level cistern using a flush volume of 6 ± 0.2 or 7 to 9 litres

no. 925, low level

Flushing volume 8 litres, side connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 926, low level

Flushing volume 6 or 9 litres, side connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 928 low level

Flushing volume 6 litres, side connection, with flush pipe, inlet valve no. 510 and provided with an interrupting flushing device.

no. 935, low level

Flushing volume 6 litres, side connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 936, low level

Flushing volume 6 litres, side- and rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 937, low level

Flushing volume 6 litres, side- and rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 950, low level

Flushing volume 6 or 9 litres, side- and rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 951, low level

Flushing volume 6 or 9 litres, side- and rear connection, with flush pipe, inlet valve 510 and flush mechanism AG-2V 951, provided with an interrupting flushing device.

Concealed flushing cisterns using a flush volume of 6 ± 0.2 litres or 7 to 9 litres

no. 980, concealed CC - 120 - L - FO - SS - L

Flushing volume 6 or 9 litre, rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 980 2V, concealed CC - 120 - L - FO - 2V - L

Flushing volume 6 or 9 litres, rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 982, concealed CC - 120 - L - TO - SS - L

Flushing volume 6 or 9 litres, rear connection, with flush pipe and inlet valve no. 510 and provided with an interrupting flushing device.

no. 983, concealed CC - 150 - S - UO - 2V - 2C

Flushing volume 6 or 9 litres, rear connection, with flush pipe, inlet valve 510 and flush mechanism 983-2V, provided with an interrupting flushing device.

no. 983C, concealed CC - 120 - S - FO - 2V - 2C

Flushing volume 6 litres, side- connection, with flush pipe, inlet valve 510 and flush mechanism 983-2V, provided with an interrupting flushing device.

no. 800, concealed CC-80-M-F0-2V-L

Flushing volume 6 or 9 litres, top inlet connection, with flush pipe, inlet valve 510 and flush mechanism PB.083.25.0000, provided with an interrupting flushing device.

Flushing cisterns

Application and use

Flushing cisterns (in combination with WC-pans) are designed as flushing devices to be connected to drinking water installations with a maximum pressure of 1000 kPa and a maximum water temperature of 30°C.

Flushing cisterns using a flush volume of 6 ± 0.2 litres are intended for use in connection with WC-pans of the type 6A, according to guideline BRL-K 619.

Marking

The Kiwa[®]-mark products are marked with the wordmark "KIWA".

Place of the mark:

- on the cistern: at the in-side above the waterline;
- on the float valve: on the body.

Compulsory specifications:

name or mark of manufacturer:

- on the cistern: on the left-side, right-side, bottom, front or above the water level on the inside of the cistern;
- on the float valve: on the body.

Method of marking:

- Non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Sanitärtechnik Eisenberg GmbH

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.